## Claims

- 1. A flexible substrate comprising:
- a connector connected to a plurality of wirings and having a plurality of electrically conducting terminals; and
- a shorting wiring interconnected for connecting to one of said plural electrically conducting terminals in said connector and for shorting to the other electrically conducting terminals.
- 2. The flexible substrate according to claim 1 wherein a hole is provided in a site surrounded by said connector and said shorting wiring.
- 3. The flexible substrate according to claim 1 wherein a pair of electrically conducting portions are provided adjacent to said shorting wiring.
- 4. The flexible substrate according to claim 2 wherein a pair of electrically conducting portions provided adjacent to said shorting wiring are provided so as to be closer to said connector than to said hole.
- 5. The flexible substrate according to claim 4 wherein a plurality of shorting wirings are further provided without interconnecting electrically conducting terminals in superposition.
- 6. The flexible substrate according to claim 5 wherein a second connector is provided at the opposite end of said wiring connecting to said connector.
- 7. An information processing apparatus including display means for making desired demonstration and a display control circuit for controlling said display means, said

apparatus comprising:

a flexible substrate including a connector connected to a plurality of wirings and having a plurality of electrically conducting terminals, and a shorting wiring interconnected for connecting to one of said plural electrically conducting terminals in said connector and for shorting to the other electrically conducting terminals; and

discriminating means for discriminating the sorts of said display means on detecting the electrically conducting state of said shorting wiring;

said display control circuit performing display control depending on the sort discriminated by said discriminating means.

- 8. The information processing apparatus according to claim 7 further comprising:
  a second connector provided at the other end of the wiring connecting to said
  connector; and
  - a cable connecting said second connector to said display means.